



Product Service

CERTIFICATE

No. Z1 18 07 12881 283

Holder of Certificate: **Zarges GmbH**Zargesstr.7
82362 Weilheim
GERMANYProduction
Facility(ies):

36773

Certification Mark:



Product:

**Standing step ladders
Z600**

Model(s):

41421 / 41422 / 41423 / 41424
41425 / 41426 / 41427 / 41428
441421 / 297601
441422 / 297602
441423 / 297603
441424 / 297604
441425 / 297605
441426 / 297606
441427 / 297607
441428 / 297608

Parameters:

max. load: 150 kg

further parameter see attachment 1.

Tested according to:

DIN EN 131-1:2016
DIN EN 131-2:2017
DIN EN 131-3:2018
EK5/AK1 17-03:2017

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 028-713102252-050

Valid until: 2023-07-10

Date, 2018-07-12

(Michael Heufelder)

Page 1 of 2





Parameter – standing step ladders Z600

Z600	standing step ladders with platform and handrail, for professional use;	
max. load :	150 kg	
art-no.	no. of steps	max. standing height
41421:	1 x 3	660 mm
41422:	1 x 4	880 mm
41423:	1 x 5	1100 mm
41424:	1 x 6	1320 mm
41425:	1 x 7	1540 mm
41426:	1 x 8	1760 mm
41427:	1 x 10	2200 mm
41428:	1 x 12	2640 mm
climbing side	stiles	steps
41421-24:	42 x 25 x 1,2/3,0 mm	80 x 35 x 1,3 mm
41425-28	48 x 25 x 1,2/3,0 mm	
supporting side:	42 x 25 x 1,2 mm	
material:	EN AW 6060	EN AW 6061
Z600	standing step ladders with platform and handrail, for professional use;	
max. load :	150 kg	
art-no.	no. of steps	max. standing height
441421 / 297601:	1 x 3	660 mm
441422 / 297602:	1 x 4	880 mm
441423 / 297603:	1 x 5	1100 mm
441424 / 297604:	1 x 6	1320 mm
441425 / 297605:	1 x 7	1540 mm
441426 / 297606:	1 x 8	1760 mm
441427 / 297607:	1 x 10	2200 mm
441428 / 297608:	1 x 12	2640 mm
climbing side	stiles	steps
441421-24 / 297601-04:	42 x 25 x 1,2/3,0 mm	80 x 35 x 1,3 mm
441425-28 / 297605-08:	48 x 25 x 1,2/3,0 mm	
supporting side:	42 x 25 x 1,2 mm	
material:	EN AW 6060	EN AW 6061

Munich, 2018-07-12